

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 1/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Slotenspray
Article number	1516701
Producttype	Mixture
Regulation	(EC) No. 1907/2006 and (EC) No. 1272/2008

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Lubricant
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV
Postbus 24
1700 AA Heerhugowaard - The Netherlands
T +31 (0)72-5765000 - F +31 (0)72-5765010
bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon : +49(0)9366-907126 (ma-do 7.15-18.00 hour) or
: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 2/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to
Regulation (EC) No. 1272/2008
[CLP]

Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Hydrocarbons, C6, isoalkanes, <5% n-hexane; Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%)



Signal word
Danger

Hazard statements

H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H411 - Toxic to aquatic life with long lasting effects
H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P391 - Collect spillage
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/ container to an approved waste disposal plant

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 3/18



Opgesteld door: NB

Bekrachtigd door: SL

Additional information

This product is exempt from the requirement for a child resistant fastening and tactile warning of danger, as it is an aspiration hazard, placed on the market in the form of an aerosol or in a container with a sealed spray attachment.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No..	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	REACH registration number
Hydrocarbons, C6,	931-254-9	64742-49-0	STOT SE 3 (H336)	-	-	-	01-2119484651-
isoalkanes, <5% n-hexane >25 - <40 %			Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) Aquatic Chronic 2 (H411) Flam Liq. 2 (H225) (EUH066)				34-XXXX
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%) 20 - <25 %	265-156-6	64742-53-6	Asp. Tox. 1 (H304)	-	-	-	01-2119480375-34
Butane 5 - <10 %	203-448-7 (601-004-00-0)	106-97-8	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119474691-32-XXXX
Isobutane 5 - <10 %	200-857-2 (601-004-00-0)	75-28-5	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	01-2119485395-27-XXXX
Hexane 0.1 - <0.5 %	203-777-6 (601-037-00-0)	110-54-3	Skin Irrit. 2 (H315) Repr. 2 (H361f) STOT SE 3 (H336) STOT RE 2 (H373) Asp. Tox. 1 (H304) Aquatic Chronic 2 (H411) Flam. Liq. 2 (H225)	STOT RE 2 :: C>=5%	1	1	01-2119480412-44-XXXX

Full text of H- and EUH-phrases: see section 16

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 4/18



Opgesteld door: NB

Bekrachtigd door: SL

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour dust/mist - mg/L	Inhalation LC50 - 4 hour vapour - mg/L	Inhalation LC50 - 4 hour gas - ppm
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9	64742-49-0	16750	3350	-	-	-
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%)	265-156-6	64742-53-6	-	-	-	-	-
Butane	203-448-7 (601-004-00-0)	106-97-8	-	-	-	-	-
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-
Hexane	203-777-6 (601-037-00-0)	110-54-3	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0	P
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%) - 64742-53-6	L
Butane - 106-97-8	C,U

Chemical name	Notes
Isobutane - 75-28-5	C,U

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 5/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention. Delayed pulmonary edema may occur.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Get immediate medical attention.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
Effects of Exposure	No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	Because of the danger of aspiration, emesis or gastric lavage should not be used unless the risk is justified by the presence of additional toxic substances.
------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO₂). Water spray.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 6/18



Opgesteld door: NB

Bekrachtigd door: SL

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 7/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials. Keep/store only in original container. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

Specific use(s)

lubricant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information

Observe technical data sheet.

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 8/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Hexane 110-54-3	TWA: 20 ppm TWA: 72 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)			
Hydrocarbons, C6, isoalkanes, <5% n-hexane (64742-49-0)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Systemic health effects Long term	Dermal	13964 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	2085 mg/m ³	

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.

Hand protection

Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374

Skin and body protection

Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection

Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type:

Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better.

Environmental exposure controls No information available.

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 9/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid	
Appearance	Aerosol	
Colour	Light yellow	
Odour	Solvent.	
Property	Values	Remarks • Method
Melting point / freezing point	Not applicable	None known
Initial boiling point and boiling range	Not applicable, Aerosol	Not applicable, Aerosol
Flammability	Not applicable for liquids	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	Not applicable, Aerosol	Not applicable, Aerosol
Autoignition temperature	>200	None known
Decomposition temperature		None known
pH	No data available	Not applicable. Insoluble in water.
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	
Water solubility	No data available.	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	0.65 - 0.72 g/cm ³	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%) = 0
VOC content approx 436.1 g/L

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 10/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products None under normal use conditions. Stable under recommended storage conditions.

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 11/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Specific test data for the substance or mixture is not available. May cause irritation.
Skin contact	Repeated exposure may cause skin dryness or cracking. Specific test data for the substance or mixture is not available. Causes skin irritation. (based on components).
Ingestion	Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause redness and tearing of the eyes. Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.
-----------------	--

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)	>5000 mg/kg
ATEmix (dermal)	>5000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	>5 mg/l
ATEmix (inhalation-vapour)	>20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C6, isoalkanes, <5% n-hexane	>16750 mg/Kg (Rattus)	>3350 mg/Kg (Oryctolagus cuniculus) OECD 402	259354 mg/m ³ (vapour) (rat OECD 403)
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%)	LD50 >5000 mg/kg (Rattus) OECD 401	LD50 > 5000 mg/kg (Oryctolagus cuniculus) OECD 402	LC50 (4h) > 5.43 mg/L (Rattus) OECD 403
Butane	-	-	=658 g/m ³ (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h
Hexane	=25 g/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=48000 ppm (Rattus) 4 h

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 12/18



Opgesteld door: NB

Bekrachtigd door: SL

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Hexane (110-54-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal		24 hours	irritant

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	European Union
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%)	^

Reproductive toxicity Based on available data, the classification criteria are not met.

The table below indicates ingredients above the cut-off threshold considered as relevant which are listed as reproductive toxins.

Chemical name	European Union
Hexane	Repr. 2

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 13/18



Opgesteld door: NB

Bekrachtigd door: SL

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	EL50 (72h) = 13.6 mg/l (Pseudokirchneriella subcapitata)	LL50 (96h) = 18.27 mg/l (Oncorhynchus mykiss)	-	EL50 (48h)= 31.9 mg/l (Daphnia magna)		
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%) 64742-53-6	EL50 (72h) > 100 mg/L (Pseudokirchneriella subcapitata) OECD 201	LL50 (96h) > 100 mg/L (Pimephales promelas)	-	EL50 (48h) > 10000 mg/L (Daphnia magna) OECD 202		
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (24h, Daphnia magna)	1	1

12.2. Persistence and degradability

Persistence and degradability No information available.

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Hydrocarbons, C6, isoalkanes, <5% n-hexane	3.6
Butane	2.31
Isobutane	2.8
Hexane	4

12.4. Mobility in soil

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 14/18



Opgesteld door: NB

Bekrachtigd door: SL

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C6, isoalkanes, <5% n-hexane	The substance is not PBT / vPvB
Distillates (petroleum), hydrotreated light naphthenic (IP346 <3%)	The substance is not PBT / vPvB
Butane	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB
Hexane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

European Waste Catalogue 16 05 04* gases in pressure containers (including halons) containing dangerous substances
15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols
14.3 Transport hazard class(es) 2
Labels 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, 2, (D), Environmentally Hazardous
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions 190, 327, 344, 625
Classification code 5F
Tunnel restriction code (D)
Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 15/18



Opgesteld door: NB

Bekrachtigd door: SL

14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols (Hydrocarbons, C6, isoalkanes, <5% n-hexane), 2.1, (0°C c.c.),
Marine pollutant
14.5 Marine pollutant P
14.6 Special precautions for user
Special Provisions 63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ) See SP277
EmS-No. F-D, S-U
14.7 Maritime transport in bulk
according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols, flammable
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards Yes
14.6 Special precautions for user
Special Provisions A145, A167, A802
Limited quantity (LQ) 30 kg G
ERG Code 10L

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 16/18



Opgesteld door: NB

Bekrachtigd door: SL

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Named dangerous substances per Seveso Directive (2012/18/EU)

Chemical name	Lower-tier requirements (tons)	Upper-tier requirements (tons)
Hydrocarbons, C6, isoalkanes, <5% n-hexane - 64742-49-0		25000

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

France

Occupational illnesses (R-463-3, France)

Chemical name	French RG number
Hydrocarbons, C6, isoalkanes, <5% n-hexane 64742-49-0	RG 84
Butane 106-97-8	RG 84
Isobutane 75-28-5	RG 84
Hexane 110-54-3	RG 59, RG 84

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 17/18



Opgesteld door: NB

Bekrachtigd door: SL

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 2B : Aerosols

Netherlands

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Chemical name	Netherlands - List of Carcinogens
Hexane 110-54-3	Fertility (Category 2)

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H336 - May cause drowsiness or dizziness

H361f - Suspected of damaging fertility

H373 - May cause damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Safety data sheets Ferney Group BV

Date : 02-07-2024
 VVFK(E) : 99/1516701
 Rev : F
 Page : 18/18



Opgesteld door: NB

Bekrachtigd door: SL

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ('Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method' Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard class

Note P: The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes.

Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)

Press. Gas (Liq.)

Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - Vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	On basis of test data
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Acute aquatic toxicity	Calculation method
Chronic aquatic toxicity	Calculation method
Aspiration hazard	Calculation method

Safety data sheets Ferney Group BV

Date : 02-07-2024
VVFK(E) : 99/1516701
Rev : F
Page : 19/18



Opgesteld door: NB

Bekrachtigd door: SL

Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)
EPA (Environmental Protection Agency)
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications
Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme
Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 13-Nov-2023

Revision note First time release

Training Advice No information available

Further information No information available

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.