Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 1/18



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Thermo-adhesive	
Article number	1516446	
Producttype	Mixture	
Regulation	(EC) No. 1907/2006 and Regulation (EC) No. 1272	

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Building and construct
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV Postbus 24 1700 AA Heerhugowaard – The Netherlands T +31 (0)72-5765000 - F +31 (0)72-5765010 bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon: +49(0)9366-907126 (ma-do 7.15-18.00 hour) or

: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government

institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 2/18



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity — single exposure	Category 3 - (H335)
Specific target organ toxicity — repeated exposure	Category 2 - (H373)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Diphenylmethane-diisocyanate, isomers and homologues

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 3/18



Opgesteld door: NB	Bekrachtigd door: SL



Signal word

Danger

Hazard statements

H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H332 - Harmful if inhaled.

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 - May cause respiratory irritation.

H351 - Suspected of causing cancer.

H373 - May cause damage to organs through prolonged or repeated exposure.

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

EUH204 - Contains isocyanates. May produce an allergic reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P260 - Do not breathe mist/vapours/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing

P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P405 - Store locked up

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to disocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

During transportation by car the cans should stand upright in the cargo space. In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam. When foaming the propellants are highly flammable. May be harmful if swallowed.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 4/18



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]		REACH registration number
Diphenylmethane-diisoc yanate, isomers and homologues	618-498-9	9016-87-9	40 - <80	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tax. 4 (H332)	STOT SE 3 :: C>=5% Skin Irrit. 2 :: C>=5% Eye Irrit. 2 :: C>=5% Resp. Sens. 1 :: C>=0.1%	[7]
Reaction products of phosphoryl trichloride and 2-methyloxirane	807-935-0	1244733-77-4	10 - <20	Acute Tox. 4 (H302) Aquatic Chronic 3 (H412)		01-2119486772- 26-XXXX
Dimethyl ether	(603-019-00- 8) 204-065-8	115-10-6	5 - <10	Flam. Gas 1 (H220) Press. Gas (H280)		01-2119472128- 37-XXXX
Isobutane	(601-004-00- 0) (601-004-01- 8) 200-857-2	75-28-5	5 - <10	Flam. Gas 1 (H220) Press. Gas (H280)		01-2119485395- 27-XXXX
Diethylene Glycol	(603-140-00- 6) 203-872-2	111-46-6	0.1 - < 0.3	Acute Tox. 4 (H302)		01-2119457857- 21-XXXX
Butane	(601-004-00- 0) (601-004-01- 8) 203-448-7	106-97-8	0.1 - <0.3	Flam. Gas 1 (H220) Press. Gas (H280)	•	01-2119474691- 32-XXXX

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Full text of H- and EUH-phrases: see section 16

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No.

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 5/18



Opgesteld door: NB	Bekrachtigd door: SL

1907/2006 (REACH), Article 59)

Notes:

See section 16 for more information

Chemical name	Notes
Dimethyl ether - 115-10-6	U
Isobutane - 75-28-5	C,U
Butane - 106-97-8	C.U

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

Inhalation Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped,

give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Get immediate medical attention.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see

a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do

not use solvents or thinners to dissolve the material.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Never give anything by

mouth to an unconscious person. Get immediate medical attention. Clean mouth with

water. Drink 1 or 2 glasses of water.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/

or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes.

Burning sensation. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors May cause sensitisation in susceptible persons. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Unsuitable extinguishing media Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE

: 17-07-2024 Date VVFK(E): 18/1516446

: A Rev : 6/18 Page



Opgesteld door: NB	Bekrachtigd door: SL

STOPPED.

5.2. Special hazards arising from the substance or mixture

chemical

Specific hazards arising from the Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation. May cause sensitisation by skin contact.

Hazardous combustion products

Carbon oxides, Carbon monoxide, Carbon dioxide (CO2), Phosphorus oxides, Nitrogen oxides (NOx). Hydrogen cyanide. Isocyanates. Halogenated compounds.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spil/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Use personal protection recommended in Section 8. For emergency responders

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Keep out of drains, sewers, ditches and waterways. Stop leak if you can do it without

risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Flood with water to complete polymerization and scrape off floor.

Take precautionary measures against static discharges. Dam up. Soak up with inert Methods for cleaning up

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment.

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 7/18



Opgesteld door: NB	Bekrachtigd door: SL

Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Keep from freezing. Keep/store only in original container. Store in a dry place. Store in a closed container. Protect from moisture.

Recommended storage

temperature

Do not freeze.

7.3. Specific end use(s)

Specific use(s)

Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Diphenylmethane-disocyanate, isomers and		TWA: 0.02 mg/m ³
homologues		STEL: 0.07 mg/m² SEN; as -NCO
9016-87-9		
Dimethyl ether	TWA: 1000 ppm	TWA: 400 ppm
115-10-6	TWA: 1920 mg/m ³	TWA: 766 mg/m ³
	-	STEL: 500 ppm
		STEL: 958 mg/m²
Diethylene Glycol		TWA: 23 ppm
111-46-6		TWA: 101 mg/m ³
		STEL: 69 ppm
		STEL: 303 mg/m ³
Butane		TWA: 600 ppm
106-97-8		TWA: 1450 mg/m²
		STEL: 750 ppm
		STEL: 1810 mg/m ³

Derived No Effect Level (DNEL) No information available

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 8/18



Opgesteld door: NB	Bekrachtigd door: SL

Derived No Effect Level (DNEL) Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	8.2 mg/m³	
worker Short term Systemic health effects	Inhalation	22.6 mg/m³	
worker Long term Systemic health effects	Dermal	2.91 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Туре	Exposure route		Safety factor
		(DNEL)	
worker	Inhalation	1894 mg/m³	
Long term	ı		
Systemic health effects			

Diethylene Glycol (111-46-6)	Diethylene Glycol (111-46-6)		
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	44 mg/m³	
worker Long term Local health effects	Inhalation	60 mg/m³	
worker Long term Systemic health effects	Dermal	43 mg/kg bw/d	

Derived No Effect Level (DNEL)			
Reaction products of phosp	horyl trichloride and 2-meth	yloxirane (1244733-77-4)	
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.45 mg/m³	
Consumer Short term Systemic health effects	Inhalation	5.6 mg/m³	
Consumer Long term Systemic health effects	Dermal	1.04 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.52 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	2 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route		Safety factor
		(DNEL)	
Consumer	Inhalation	471 mg/m³	

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 9/18

Long term



Opgesteld door: NB	Bekrachtigd door: SL

Systemic health effects			
Diethylene Glycol (111-46-6)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	12 mg/m³	
Consumer Long term Local health effects	Inhalation	12 mg/m³	
Consumer Long term Systemic health effects	Dermal	21 mg/kg	

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)		
Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	0.32 mg/l	
Marine water	0.032 mg/l	
Sewage treatment plant	19.1 mg/l	
Freshwater sediment	11.5 mg/kg dry weight	
Marine sediment	1.15 mg/kg dry weight	
Soil	0.34 mg/kg dry weight	
Freshwater - intermittent	0.51 mg/l	

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

Diethylene Glycol (111-46-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Sewage treatment plant	199 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Marine sediment	2.09 mg/kg dry weight
Boil	1.53 mg/kg dry weight
Freshwater - intermittent	10 mg/l

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be

exhausted directly at the point of origin.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Butyl rubber. Nitrile rubber. Glove thickness > 0.4 mm. The

breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general

greater than 60 min. Gloves must conform to standard EN 374

Skin and body protection Wear appropriate personal protective clothing to prevent skin contact.

: 17-07-2024 Date VVFK(E): 18/1516446

Rev : A **Page** : 10/18



Bekrachtigd door: SL Opgesteld door: NB

Respiratory protection Ensure adequate respiratory protection during spray applications. In case of insufficient

ventilation, wear suitable respiratory equipment

Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming Recommended filter type:

Not applicable, Aerosol

to EN 140 with Type A filter or better. AX.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Aerosol Foam Appearance Colour

Characteristic, Slight. Odour No information available Odour threshold

Property Melting point / freezing point Values Not applicable . °C Remarks • Method

None known

Initial boiling point and boiling Not applicable, Aerosol ... Not applicable, Aerosol range

Flammability

Not applicable for liquids . None known Flammability Limit in Air None known

Upper flammability or explosive 18.6 Vol%

limits

Lower flammability or explosive 1.7 Vol% limits.

Not applicable, Aerosol . Flash point

No data available None known Autoignition temperature

Decomposition temperature None known

No data available None known. pH (as aqueous solution) No data available None known Kinematic viscosity No data available None known

No data available Dynamic viscosity Water solubility Immiscible in water.

Solubility(les) No data available None known Partition coefficient No data available None known 6.7 bar @ 23 °C Vapour pressure Relative density No data available None known

Bulk Density No data available Density 1.002 g/cm^a

No data available None known Relative vapour density

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Minimum Ignition Temperature 235 Not applicable .

SECTION 10: Stability and reactivity

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 11/18



Opgesteld door: NB	Bekrachtigd door: SL

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions. Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Product cures with moisture. Heat, flames and sparks. Excessive heat. Do not freeze.

Protect from moisture. Keep away from open flames, hot surfaces and sources of

ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines.

Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of

respiratory tract. Harmful by inhalation.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

irritation. (based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged

skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. May cause additional

affects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation,

nausea, vomiting and diarrhoea. May be harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing,

tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 12/18



Opgesteld door: NB	Bekrachtigd door: SL

redness and tearing of the eyes.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 4,361.60 mg/kg

ATEmix (dermal) >5000 mg/kg

ATEmix (inhalation-gas) >20000 ppm

ATEmix (inhalation-vapour) >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane-diisocyanate,	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg	=1.5 mg/L (Rattus) 4 h
isomers and homologues		(Oryctolagus cuniculus)	
Reaction products of	LD50 > 500 - 2000 mg/kg	LD50 >2000 mg/Kg (Rattus)	LD50 > 7 mg/L (4h)(Rattus)
phosphoryl trichloride and	(males); LD50 = 632 mg/kg	(OECD 402)	(OECD 403)
2-methyloxirane	(females)(Rattus)		,
Dimethyl ether			=164000 ppm (Rattus) 4 h
Isobutane			=658 mg/L (Rattus) 4 h
Diethylene Glycol	=1120 mg/kg bw (human)	= 11890 mg/kg (Oryctolagus	LC0 (4h)> 4600 mg/m ³ (
		cuniculus)	Rattus)
Butane			=658 g/m3 (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit				Mild skin irritant
Acute Dermal					
Irritation/Corrosion					

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 404	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 405	Rabbit	eye			Non-irritant

Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		sensitising
Sensitisation: Local Lymph Node			_
Assay			

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 13/18



Opgesteld door: NB	Bekrachtigd door: SL

	Species	Exposure route	Results
OECD Test No. 429: Skin	Mouse		Did not cause sensitisation on
Sensitisation: Local Lymph Node			laboratory animals
Assay			

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

Component Information

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

	Species	Results
OECD Test No. 453: Combined Chronic	Rat	Carcinogenic
Toxicity/Carcinogenicity Studies		

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diphenylmethane-diiso	ErC50 (72h)	CL50 (96h)		EC50 (24H)		
cyanate, isomers and	>1640 mg/L	>1000 mg/L	l .	>1000 mg/L		
homologues	Algae	(Danio rerio)	l .	Daphnia magna		
9016-87-9	(scenedesmus		l .			
1	subspicatus)	l	l .			
	(OECD 201)					
	EC50 (72h) = 82	LC50 (96h) = 51		LC50 (48h) =		
phosphoryl trichloride	mg/L	mg/L	l .	131 mg/L		
and 2-methyloxirane	(Pseudokirchner	(Pimephales	l .	Daphnia magna		
1244733-77-4	iella	promelas) Static				

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 14/18



Opgesteld door: NB	Bekrachtigd door: SL

	subcapitata) OECD 201				
Dimethyl ether		LC50: >4.1g/L		> 4400 mg/L	
115-10-6		(96h, Poecilia	l .	(Daphnia) (NEN	l
		reticulata)		6501)	
Diethylene Glycol 111-46-6		LC50: =75200mg/L (96h,	•	EC50: =84000mg/L (48h, Daphnia	
		Pimephales promelas)		magna)	

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)

Method	Exposure time	Value	Results
		0% biodegradation	Not readily biodegradable
Biodegradability: Modified MITI Test			
(II)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Reaction products of phosphoryl trichloride and	2.68
2-methyloxirane	
Dimethyl ether	-0.18
Isobutane	2.8
Diethylene Glycol	-1.98
Butane	2.31

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Reaction products of phosphoryl trichloride and 2-methyloxirane	The substance is not PBT / vPvB
Dimethyl ether	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB PBT assessment does
	not apply
Diethylene Glycol	The substance is not PBT / vPvB PBT assessment does
	not apply
Butane	The substance is not PBT / vPvB PBT assessment does
	not apply

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

: 17-07-2024 **Date** VVFK(E): 18/1516446

Rev : A : 15/18 **Page**



Bekrachtigd door: SL Opgesteld door: NB

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or

European Waste Catalogue

08 05 01* waste isocyanates 16 05 04* gases in pressure containers (including halons) containing dangerous

17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03

Other information

Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Note: Keep from freezing

Land transport (ADR/RID) 14.1 UN number or ID number UN1950 14.2 Proper Shipping Name Aerosols 14.3 Transport hazard class(es) Labels 2.1

14.4 Packing group

Not regulated UN1950, Aerosols, 2, (D) Description Not applicable

14.5 Environmental hazards

14.6 Special precautions for user

190, 327, 344, 625 Special Provisions

Classification code 5E (D) Tunnel restriction code Limited quantity (LQ) 1 L

IMDG 14.1 UN number or ID number UN1950 14.2 Proper Shipping Name 14.3 Transport hazard class(es) Aerosols 2.1

14.4 Packing group Not regulated UN1950, Aerosols, 2.1 Description

14.5 Marine pollutant

14.6 Special precautions for user

Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277 EmS-No

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

UN1950 14.1 UN number or ID number

14.2 Proper Shipping Name Aerosols, flammable 14.3 Transport hazard class(es)

14.4 Packing group

Description UN1950, Aerosols, flammable, 2.1

Not applicable 14.5 Environmental hazards

: 17-07-2024 Date VVFK(E): 18/1516446

Rev : A : 16/18 **Page**



Opgesteld door: NB	Bekrachtigd door: SL

14.6 Special precautions for user

A145, A167, A802 Special Provisions

Limited quantity (LQ) 30 kg G **ERG Code** 10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Chemical name	CAS No	Restricted substance per REACH
		Annex XVII
Diphenylmethane-disocyanate, isomers and homologues	9016-87-9	56
		74.
Discoyantes	-	74

^{56.} If product supplied to the general public with substance ≥0.1%, then gloves must be provided with the product. 74 If product supplied to the industrial or professional users with total monomeric diisocyanates ≥ 0.1%, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS P3b - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 17/18



Opgesteld door: NB	Bekrachtigd door: SL

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

H302 - Harmful if swallowed

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H332 - Harmful if inhaled

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 - May cause respiratory irritation

H351 - Suspected of causing cancer

H373 - May cause damage to organs through prolonged or repeated exposure

H412 - Harmful to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

Legend

TWA TWA (time-weighted average)
STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals VPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 08-Mar-2023

Indication of changes

Revision note Not applicable.

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE

INDUSTRIAL OR PROFESSIONAL USE

Further information No information available

Date : 17-07-2024 VVFK(E) : 18/1516446

Rev : A Page : 18/18



Opgesteld door: NB	Bekrachtigd door: SL

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.