Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 1/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Power cleaner
Article number	1516715
Producttype	Mixture
Regulation	(EC) No. 1907/2006 and (EC) No. 1272/2008

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Surface cleaning Detergent
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV Postbus 24 1700 AA Heerhugowaard – The Netherlands T +31 (0)72-5765000 - F +31 (0)72-5765010 bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon: +49(0)9366-907126 (ma-do 7.15-18.00 hour) or

: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government

institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 2/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aspiration hazard	Category 1 - (H304)
Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Specific target organ toxicity — single exposure	Category 3 - (H336)
Category 3 Narcotic effects	
Chronic aquatic toxicity	Category 2 - (H411)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclic, <5% n-hexane; Acetone



Signal word Danger

Hazard statements

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P251 - Do not pierce or burn, even after use

P261 - Avoid breathing vapours/spray

P271 - Use only outdoors or in a well-ventilated area

P280 - Wear protective gloves and eye/face protection

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312 - Call a POISON CENTER or doctor/physician if you feel unwell

P391 - Collect spillage

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 3/20



Opgesteld door: NB	Bekrachtigd door: SL

Additional information

This product is exempt from the requirement for a child resistant fastening and tactile warning of danger, as it is an aspiration hazard, placed on the market in the form of an aerosol or in a container with a sealed spray attachment.

2.3. Other hazards

In case of insufficient ventilation and/or through use, the formation of a explosive/highly flammable mixture is possible.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU	CAS No	Classification	Specific	M-Factor	M-Factor	REACH
	Index No).		according to	concentration limit		(long-ter	registration
			•				
			Regulation (EC) No.	(SCL)		m)	number
			1272/2008 [CLP]				
Hydrocarbons, C7,	927-510-4	RR-100219-3	STOT SE 3 (H336)	-	-	-	01-2119475515-
n-alkanes, isoalkanes,	l .		Asp. Tox. 1 (H304)				33-xxxx
cyclics	l .		Skin Irrit. 2 (H315)				
40 - <80 %	l .		Aquatic Chronic 2				
	l .		(H411)				
			Flam. Liq. 2 (H225)				
Acetone	200-662-2	67-64-1	Eye Irrit. 2 (H319)	-	-	-	01-2119471330-
10 - <20 %	(606-001-00-		(EUH066)				49-XXXX
	8)		STOT SE 3 (H336)				
	,		Flam. Liq. 2 (H225)				
Carbon dioxide	204-696-9	124-38-9	Press. Gas (H281)	-	-	-	[4]
1 - <5 %			,				
Butane	203-448-7	106-97-8	Flam. Gas 1 (H220)	-	-	-	01-2119474691-
1 - <5 %	(601-004-00-		Press. Gas (H280)				32-XXXX
	0)		, ,				
Isobutane	200-857-2	75-28-5	Flam. Gas 1 (H220)		-	-	01-2119485395-
1 - <2.5 %	(601-004-00-		Press. Gas (H280)				27-XXXX
	0)		, , , , ,				

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Full text of H- and EUH-phrases: see section 16

NOTE [4] - This substance is exempted from registration according to the provisions of Article 2(7)(a) and Annex IV of REACH

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 4/20



Opgesteld door: NB	Bekrachtigd door: SL

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	LC50 - 4 hour -	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	927-510-4	RR-100219-3	•	•	•	•	-
Acetone	200-662-2 (606-001-00-8)	67-64-1	5800	-	-	-	-
Carbon dioxide	204-696-9	124-38-9	-	-	-	-	-
Butane	203-448-7 (601-004-00-0)	106-97-8	-	-	-	-	-
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

Notes

See section 16 for more information

Chemical name	Notes
Butane - 106-97-8	C,U
Isobutane - 75-28-5	C,U

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 5/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is

required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Get immediate medical attention.

Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get medical attention if irritation develops and

persists.

Skin contact Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective

equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and

tearing of the eyes. Burning sensation. Inhalation of high vapour concentrations may

cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Effects of Exposure No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Because of the danger of aspiration, emesis or gastric lavage should not be used unless

the risk is justified by the presence of additional toxic substances.

: 03-07-2024 Date VVFK(E) : 18/1516715

Rev : c **Page** : 6/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED. Unsuitable extinguishing media

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Cylinders may rupture under extreme heat. Damaged cylinders should be handled only

by specialists. Containers may explode when heated. Hazardous combustion products Carbon oxides, Carbon monoxide, Carbon dioxide (CO2),

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

> section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take

precautionary measures against static discharges. Avoid breathing

dust/fume/gas/mist/vapours/spray.

Ventilate the area. Refer to protective measures listed in Sections 7 and 8. Other information

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce

vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 7/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Store away from other materials. Keep/store only in original container. Store in a dry place. Store in a closed container.

7.3. Specific end use(s)

Specific use(s)

Detergent. Surface cleaning.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 8/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union	
Acetone	TWA: 500 ppm	
67-64-1	TWA: 1210 mg/m ³	
Carbon dioxide	TWA: 5000 ppm	
124-38-9 TWA: 9000 mg/m ³		

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL) Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
worker Long term Systemic health effects	Inhalation	2085 mg/m³		
worker Long term Systemic health effects	Dermal	300 mg/kg bw/d		

Acetone (67-64-1)			
Гуре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
ong term Systemic health effects vorker	Dermal	186 mg/kg bw/d	
Short term Local health effects worker	Inhalation	2420 mg/m³	
ong term	Inhalation	1210 mg/m³	
Systemic health effects worker			

Date : 03-07-2024 VVFK(E): 18/1516715

Rev **Page** : 9/20



Opgesteld door: NB	Bekrachtigd door: SL

Derived No Effect Level (DNEL)					
Hydrocarbons, C7, n-alkanes	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
Consumer Long term Systemic health effects	Inhalation	447 mg/m³			
Consumer Long term Systemic health effects	Dermal	149 mg/kg bw/d			
Consumer Long term Systemic health effects	Oral	149 mg/kg bw/d			

Acetone (67-64-1)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer	Inhalation	200 mg/m ³	
Long term Systemic health effects			
Consumer	Dermal	62 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Oral	62 mg/kg bw/d	
Long term			
Systemic health effects			

Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)			
Acetone (67-64-1)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	10.6 mg/l		
Freshwater - intermittent	21 mg/l		
Marine water	1.06 mg/l		
Microorganisms in sewage treatment	100 mg/l		
Freshwater sediment	30.4 mg/kg dry weight		
Marine water	3.04 mg/kg dry weight		
Soil	29.5 mg/kg dry weight		

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be **Engineering controls**

exhausted directly at the point of origin.

Personal protective equipment

Wear safety glasses with side shields (or goggles). Eye protection must conform to Eye/face protection

standard EN 166.

Hand protection Wear suitable gloves. Glove thickness > 0.7mm. Butyl rubber. Nitrile rubber. The

breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform

to standard EN 374

Skin and body protection

Wear appropriate personal protective clothing to prevent skin contact.

Respiratory protection Ensure adequate respiratory protection during spray applications. In case of insufficient

: 03-07-2024 Date VVFK(E): 18/1516715

Rev : c : 10/20 **Page**



Bekrachtigd door: SL Opgesteld door: NB

ventilation, wear suitable respiratory equipment.

Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming Recommended filter type:

to EN 140 with Type A filter or better.

Environmental exposure controls No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Aerosol Colour Colourless Petroleum. Odour

Values Remarks • Method Property

Melting point / freezing point No data available None known

Initial boiling point and boiling Not applicable, Aerosol . Not applicable, Aerosol

range

Flammability Not applicable for liquids . None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Not applicable, Aerosol . Not applicable, Aerosol Flash point

Autoignition temperature >200 None known None known

Decomposition temperature

No data available Not applicable. Insoluble in water.

No data available None known pH (as aqueous solution) No data available Kinematic viscosity None known

No data available Dynamic viscosity

Water solubility No data available. None known Solubility(ies) No data available None known No data available Partition coefficient None known No data available Vapour pressure None known Relative density No data available None known

No data available **Bulk Density** Density 0.65 - 0.75 g/cm3

Relative vapour density No data available None known

Particle characteristics

Particle Size No information available **Particle Size Distribution** No information available

9.2. Other information

Solid content (%) 0

approx 682.0 g/L VOC content

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 11/20



Opgesteld door: NB Bekrachtigd door: SL

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

mpact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Heating causes rise in pressure with risk of bursting.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of

ignition. Extremes of temperature and direct sunlight.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents. Incompatible with oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 12/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal. Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation.

Causes serious eye irritation. (based on components). May cause redness, itching, and

pain.

Skin contact Repeated exposure may cause skin dryness or cracking. Specific test data for the

substance or mixture is not available. Causes skin irritation. (based on components).

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may

cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. Redness. May cause

redness and tearing of the eyes. Inhalation of high vapour concentrations may cause

symptoms like headache, dizziness, tiredness, nausea and vomiting.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 >5000 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	LD50 >5840 mg/kg Rat	LD50 >2920 mg/kg (Rattus)	LC50 >23.3 mg/L (4h)(Rat, vapour) (OECD 403)
Acetone	=5800 mg/kg (Rattus) 3000 mg/Kg (mouse)	>15800 mg/Kg (Rattus)	=79 mg/l(Rattus) 4 h
Butane	-	-	=658 g/m3 (Rattus) 4 h
Isobutane	-	-	=658 mg/L (Rattus) 4 h

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 13/20



Opgesteld door: NB	Bekrachtigd door: SL

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Acetone (67-64-1)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Acetone (67-64-1)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	Not a skin sensitiser
Sensitisation			

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 14/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Hydrocarbons, C7,	ErL50 (72h) =	LL50 (96h)	-	EL50 (48h) =		
n-alkanes, isoalkanes,	10-30 mg/L	>13.4 mg/L		3.0 mg/L		
cyclics	(Pseudokirchner	(Oncorhynchus		(Daphnia		
RR-100219-3	iella subcapitata)	mykiss)		magna)		
		OECD 203				
Acetone	-	LC50 96 h 4.74	EC50 = 14500	EC50 48 h		
67-64-1		- 6.33 mL/L	mg/L 15 min	10294 - 17704		
		(Oncorhynchus		mg/L (Daphnia		
		mykiss)		magna Static)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (RR-100219-3)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready	28 days	98%	Readily biodegradable
Biodegradability: Manometric	_		
Respirometry Test (TG 301 F)			

Acetone (67-64-1)

10010110 (01 01 1)			
Method	Exposure time	Value	Results
OECD Test No. 301B: Ready	28 days	biodegradation	91 % Readily biodegradable
Biodegradability: CO2 Evolution Test	t -		
(TG 301 B)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

compensation morniagen		
Chemical name	Partition coefficient	
Acetone	-0.24	
Butane	2.31	
Isobutane	2.8	

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

: 03-07-2024 **Date** VVFK(E): 18/1516715

Rev : c **Page** : 15/20



Opgesteld door: NB	Bekrachtigd door: SL

PBT and vPvB assessment

The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	The substance is not PBT / vPvB
Acetone	The substance is not PBT / vPvB
Butane	The substance is not PBT / vPvB
Isobutane	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or

weld containers.

16 05 04* gases in pressure containers (including halons) containing dangerous **European Waste Catalogue**

substances

15 01 04 metallic packaging

Waste codes should be assigned by the user based on the application for which the Other information

product was used.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 16/20



Opgesteld door: NB Bekrachtigd door: SL

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number
14.2 UN proper shipping name
14.3 Transport hazard class(es)
Labels
UN 1950
Aerosols
2
2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2, (D), Environmentally Hazardous

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions 190, 327, 344, 625

Classification code 5F Tunnel restriction code (D) Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols
14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics), 2.1, (0°C c.c.),

Marine pollutant

14.5 Marine pollutant F

14.6 Special precautions for user

Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277 EmS-No. F-D. S-U

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 UN proper shipping name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, flammable, 2.1

14.5 Environmental hazards Yes

14.6 Special precautions for user

Special Provisions A145, A167, A802

Limited quantity (LQ) 30 kg G ERG Code 10L

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 17/20



Opgesteld door: NB	Bekrachtigd door: SL

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

E2 - Hazardous to the Aquatic Environment in Category Chronic 2

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

This product contains

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 18/20



Opgesteld door: NB	Bekrachtigd door: SL

Chemical name	Reporting of suspicious transactions, disappearances and thefts	Restricted
Acetone - 67-64-1	X	

Regulation (EC) No. 648/2004 (Detergents regulation)

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons	>= 30%

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Acetone	RG 84
67-64-1	
Carbon dioxide 124-38-9	RG 5,RG 14,RG 15,RG 15bis,RG 20bis
Butane 106-97-8	RG 84
Isobutane 75-28-5	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 2B : Aerosols

<u>Netherlands</u>

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 19/20



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H281 - Contains refrigerated gas; may cause cryogenic burns or injury

H304 - May be fatal if swallowed and enters airways

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H411 - Toxic to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (Table 3): When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.)

Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Single exposure EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value Sk* Skin designation

Date : 03-07-2024 VVFK(E) : 18/1516715

Rev : c Page : 20/20



Opgesteld door: NB	Bekrachtigd door: SL

Classification procedure		
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used	
Acute oral toxicity	Calculation method	
Acute dermal toxicity	Calculation method	
Acute inhalation toxicity - gas	Calculation method	
Acute inhalation toxicity - Vapour	Calculation method	
Acute inhalation toxicity - dust/mist	Calculation method	
Skin corrosion/irritation	On basis of test data	
Serious eye damage/eye irritation	On basis of test data	
Respiratory sensitisation	Calculation method	
Skin sensitisation	Calculation method	
mutagenicity	Calculation method	
Carcinogenicity	Calculation method	
Reproductive toxicity	Calculation method	
STOT - single exposure	Calculation method	
STOT - repeated exposure	Calculation method	
Acute aquatic toxicity	Calculation method	
Chronic aquatic toxicity	Calculation method	
Aspiration hazard	Calculation method	
Ozone	Calculation method	
Flammable aerosol	On basis of test data	

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

EPA (Environmental Protection Agency)

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 14-Nov-2023

Revision note First time release

Training Advice No information available

Further information No information available

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.