Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 1/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Silikit remover
Article number	1516300
Producttype	Mixture
Regulation	(EC) No. 1907/2006 and (EC) No. 1272/2008

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Cleaning agent
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV Postbus 24 1700 AA Heerhugowaard – The Netherlands T +31 (0)72-5765000 - F +31 (0)72-5765010 bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon: +49(0)9366-907126 (ma-do 7.15-18.00 hour) or

: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government

institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 2/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation	Category 1 Sub-category C - (H314)
Serious eye damage/eye irritation	Category 1 - (H318)
Flammable liquids	Category 3 - (H226)

2.2. Label elements

Contains Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives



Signal word

Danger

Hazard statements

H314 - Causes severe skin burns and eye damage

H226 - Flammable liquid and vapour

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P260 - Do not breathe vapour

P280 - Wear protective gloves/protective clothing and eye/face protection

P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor

P370 + P378 - In case of fire: Use dry chemical, CO2, water spray or alcohol-resistant foam to extinguish

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires child resistant fastenings if supplied to the general public. This product requires tactile warnings if supplied to the general public.

2.3. Other hazards

Harmful to aquatic life.

PBT & vPvE

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

Endocrine Disruptor Information This product does not contain any known or suspected endocrine disruptors.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 3/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No).	CAS No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-ter m)	REACH registration number
Hydrocarbons, C11-C12, isoalkanes <2% aromatics 40 - <80 %	918-167-1	RR-99779-5	Asp. Tox. 1 (H304) (EUH066) Flam. Liq. 3 (H226)	-	-	-	01-2119472146- 39-XXXX
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives 10 - <20 %	287-494-3	85536-14-7	Skin Corr. 1C (H314) Acute Tox. 4 (H302) Eye Dam. 1(H318) Aquatic Chronic 3 (H412)	-	-	-	01-2119490234- 40-XXXX
Isopropyl alcohol 0.1- <1 %	200-661-7 (603-117-00-	67-63-0	Eye Irrit. 2 (H319) STOT SE 3 (H336)	-	-	-	01-2119457558- 25-XXXX
	0)		Flam. Liq. 2 (H225)				
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides 0.1-<1 %	263-081-3	61789-72-8	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Acute Tox. 4 (H302) Aquatic Acute 1 (H400)	-	•		01-2119970169- 28-XXXX
Methyl ethyl ketone 0.1 - <0.3 %	201-159-0 (606-002-00- 3)	78-93-3	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Lig. 2 (H225)	-	•	•	01-2119457290- 43-XXXX

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 4/22



Opgesteld door: NB	Bekrachtigd door: SL

Chemical name	EC No (EU Index No)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Hydrocarbons, C11-C12, isoalkanes <2% aromatics	918-167-1	RR-99779-5	•	•	•	•	•
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	287-494-3	85536-14-7	1219	•	•	,	,
Isopropyl alcohol	200-661-7 (603-117-00-0)	67-63-0	-	-	-	•	•
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, chlorides	263-081-3	61789-72-8	500	-	-	-	-
Methyl ethyl ketone	201-159-0 (606-002-00-3)	78-93-3	-	-	-	-	-

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical

attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get immediate

: 25-06-2024 Date VVFK(E) : 05/1516300

: E Rev : 5/22 **Page**



Opgesteld door: NB	Bekrachtigd door: SL

medical attention.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Eye contact

Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical attention.

Wash off immediately with soap and plenty of water while removing all contaminated Skin contact

clothes and shoes. Get immediate medical attention.

Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious Ingestion

person. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the

> material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use

barrier to give mouth-to-mouth resuscitation.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation.

No information available. Effects of Exposure

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Product is a corrosive material. Use of gastric lavage or emesis is contra-indicated.

Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood

pressure may occur with moist rales, frothy sputum, and high pulse pressure.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media No information available.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Silicon dioxide. Thermal decomposition can lead to release of irritating

and toxic gases and vapours.

5.3. Advice for firefighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 6/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure

adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material. Attention! Corrosive material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or

spillage if safe to do so. Prevent product from entering drains. Should not be released

into the environment. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A

vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labelled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 7/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapours or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Protect from

moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

7.3. Specific end use(s)

Specific use(s) Cleaning agent.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 8/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Only European Community Occupational Exposure Limits will be shown in this document. Please refer to regional SDS for further information.

Chemical name	European Union
Silica, amorphous 7631-86-9	TWA: 0.1 mg/m ³
Methyl ethyl ketone	TWA: 200 ppm
78-93-3	TWA: 600 mg/m ³ STEL: 300 ppm
	STEL: 900 mg/m ³

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL) Isopropyl alcohol (67-63-0)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	500 mg/m³	
worker Long term Systemic health effects	Dermal	888 mg/kg bw/d	

Methyl ethyl ketone (78-93-3)			
Туре	Exposure route	Derived No Effect Level	Safety factor
		(DNEL)	
worker	Dermal	1161 mg/kg bw/d	
Long term			
Systemic health effects			
worker	Inhalation	600 mg/m ³	
Long term			
Systemic health effects	1		1

Derived No Effect Level (DNEL)			
Isopropyl alcohol (67-63-0)			
Туре	Exposure route	1	Safety factor
		(DNEL)	
Consumer	Inhalation	89 mg/m³	
Long term			
Systemic health effects			
Consumer	Dermal	319 mg/kg bw/d	

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 9/22



Opgesteld door: NB	Bekrachtigd door: SL

Long term Systemic health effects			
Consumer	Oral	26 mg/kg bw/d	
Long term			
Systemic health effects			

Methyl ethyl ketone (78-93-3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	106 mg/m ³	
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d	

Predicted No Effect Concentration No information available. (PNEC)

Predicted No Effect Concentration (PNEC)		
Isopropyl alcohol (67-63-0)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	140.9 mg/l	
Marine water	140.9 mg/l	
Sewage treatment plant	2251 mg/l	
Freshwater sediment	552 mg/kg dry weight	
Marine sediment	552 mg/kg dry weight	
Soil	28 mg/kg dry weight	

Methyl ethyl ketone (78-93-3)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	55.8 mg/l	
Marine water	55.8 mg/l	
Freshwater sediment	287.74 mg/l	
Marine sediment	287.7 mg/l	
Soil	22.5 mg/l	

8.2. Exposure controls

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear protective gloves. Gloves must conform to standard EN 374. Recommended Use:.

Nitrile rubber. Glove thickness >= 0.15 mm.

Skin and body protection Respiratory protection Suitable protective clothing.

In case of insufficient ventilation, wear suitable respiratory equipment.

Recommended filter type: Type A.

Environmental exposure controls No information available.

: 25-06-2024 Date VVFK(E): 05/1516300

: E Rev : 10/22 **Page**



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Liquid Colour Brown

Odour Characteristic.

Remarks • Method Property <u>Values</u>

Melting point / freezing point -25 °C None known 36 °C None known Initial boiling point and boiling

range

Flammability No data available Flammable liquid Flammability Limit in Air None known

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

<= 60 °C None known Flash point Autoignition temperature ~310 None known Decomposition temperature None known No data available None known. No data available pH (as aqueous solution) None known None known

> 21 mm²/s Kinematic viscosity Dynamic viscosity 140000 mPas

Water solubility No data available. None known No data available Solubility(ies) None known Partition coefficient No data available None known Vapour pressure No data available None known No data available Relative density None known

Bulk Density No data available

Liquid Density 0.81

No data available Relative vapour density None known

Particle characteristics

Particle Size No information available Particle Size Distribution No information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 11/22



Opgesteld door: NB Bekrachtigd door: SL

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

10.5. Incompatible materials

Incompatible materials Acids. Bases. Oxidising agent.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 12/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Corrosive by inhalation.

(based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic

edema of the lungs. Pulmonary edema can be fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye

damage. (based on components). Corrosive to the eyes and may cause severe damage

including blindness. May cause irreversible damage to eyes.

Skin contact Prolonged skin contact causes burns. Symptoms may be delayed. May cause irritation.

Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on

components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause

lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 8,181.20 mg/kg

 ATEmix (dermal)
 >5000 mg/kg

 ATEmix (inhalation-gas)
 >20000 ppm

 ATEmix (inhalation-dust/mist)
 >5 mg/l

 ATEmix (inhalation-vapour)
 >20 mg/l

Component Information

Chemical name Oral LD50	Dermal LD50	Inhalation LC50
-------------------------	-------------	-----------------

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 13/22



Opgesteld door: NB	Bekrachtigd door: SL

Hydrocarbons, C11-C12, isoalkanes <2% aromatics	LD50 >5000mg/Kg (Rattus)	LC50 >5000 mg/Kg (Oryctolagus cuniculus) (OECD 402)	LC50 >5000 mg/m³ (Rattus) (OECD 403)
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	=1219 mg/kg (Rattus)	LD50 >2000 mg/Kg (Rattus)	-
Isopropyl alcohol	>5000 mg/Kg	= 4059 mg/kg (Oryctolagus cuniculus)	=72600 mg/m³ (Rattus) 4 h
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Causes serious eye damage. Causes burns. Classification based on data available for

ingredients.

Isopropyl alcohol (67-63-0)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			Irritant
Acute Eye		·			
Irritation/Corrosion					

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion	1				

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Component Information Isopropyl alcohol (67-63-0)

Method	Species	Results
OECD Test No. 476: In vitro Mammalian Cell	Hamster, in vitro	Not mutagenic
Gene Mutation Test		

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 14/22



Opgesteld door: NB	Bekrachtigd door: SL

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 15/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life.

Chemical name	Algae/aquatic	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
						(long-term)
Benzenesulfonic acid,	EC50: =36mg/L	LC50: =5.6mg/L	-	EC50: =5.2mg/L		
4-C10-13-sec-alkyl	(72h,	(96h, Cyprinus		(48h, Daphnia		
derivatives	Desmodesmus	carpio)		magna)		
85536-14-7	subspicatus)	. ,				
Isopropyl alcohol	EC50 72 h >	LC50 96 h >	-	EC50:		
67-63-0	1000 mg/L	1400000 ?g/L		=13299mg/L		
	(Desmodesmus	(Lepomis		(48h, Daphnia		
	`subspicatus)	macrochirus)		magna)		
Methyl ethyl ketone	EC50=1972 mg/l	LC50: 3130 -	EC50 = 3403	EC50 48 h > 308		
78-93-3	(Pseudokirchner	3320mg/L (96h,	mg/L 30 min	mg/L (Daphnia		
	iella subcapitata)	Pimephales	EC50 = 3426	magna)		
		promelas)	mg/L 5 min			

12.2. Persistence and degradability

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)

Weatly ethy ketone (70-55-5)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready	28 days	biodegradation	98 % Readily biodegradable
Biodegradability: Closed Bottle Test	-		
(TG 301 D)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	2.2
Isopropyl alcohol	0.05
Methyl ethyl ketone	0.3

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the

threshold of declaration.

Chemical name	PBT and vPvB assessment
Hydrocarbons, C11-C12, isoalkanes <2% aromatics	The substance is not PBT / vPvB

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 16/22



Opgesteld door: NB	Bekrachtigd door: SL

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivatives	The substance is not PBT / vPvB
Isopropyl alcohol	The substance is not PBT / vPvB
Methyl ethyl ketone	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

: 25-06-2024 Date VVFK(E) : 05/1516300

: E Rev : 17/22 **Page**



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or Contaminated packaging

weld containers.

Waste codes should be assigned by the user based on the application for which the Other information

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID number UN2924

14.2 UN proper shipping name Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid,

4-C10-13-sec-alkyl derivatives)

14.3 Transport hazard class(es)

Labels

3 3 + 8

14.4 Packing group

Description UN2924, Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid,

Not applicable

4-C10-13-sec-alkyl derivatives), 3 (8), III, (D/E)

14.5 Environmental hazards

14.6 Special precautions for user

Special Provisions 274 FC Classification code Tunnel restriction code (D/E) Limited quantity (LQ) 5 L ADR Hazard Id (Kemmler

Number)

38

UN2924 14.1 UN number or ID number

Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid, 14.2 UN proper shipping name

4-C10-13-sec-alkyl derivatives)

14.3 Transport hazard class(es) 8 Subsidiary hazard class

14.4 Packing group

UN2924, Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid, Description

4-C10-13-sec-alkyl derivatives), 3 (8), III, (60°C c.c.)

14.5 Marine pollutant

14.6 Special precautions for user

223, 274 Special Provisions Limited Quantity (LQ)

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 18/22



Opgesteld door: NB	Bekrachtigd door: SL

EmS-No. F-E, S-C

14.7 Maritime transport in bulk according to IMO instruments

Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN2924

14.2 UN proper shipping name Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid,

4-C10-13-sec-alkyl derivatives)

14.3 Transport hazard class(es) 3 Subsidiary hazard class 8 14.4 Packing group

Description UN2924, Flammable liquid, corrosive, n.o.s (Isopropyl alcohol, Benzenesulfonic acid,

4-C10-13-sec-alkyl derivatives), 3 (8), III

14.5 Environmental hazards Not applicable

14.6 Special precautions for user

Special Provisions A3, A803 Limited quantity (LQ) 1 L ERG Code 3C

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 19/22



Opgesteld door: NB	Bekrachtigd door: SL

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)

P5a - FLAMMABLE LIQUIDS P5b - FLAMMABLE LIQUIDS P5c - FLAMMABLE LIQUIDS

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 20/22



Opgesteld door: NB	Bekrachtigd door: SL

Not applicable

Regulation (EC) No. 648/2004 (Detergents regulation)

Labelling for contents according to regulation (EC) No. 648/2004

>= 30% aliphatic hydrocarbons	
5 - < 15% anionic surfactants	
< 5% cationic surfactants	
< 5% Isopropyl alcohol	

National regulations

France

Occupational Illnesses (R-463-3, France)

Chemical name	French RG number
Isopropyl alcohol 67-63-0	RG 84
Methyl ethyl ketone 78-93-3	RG 84

Germany

Ordinance on Industrial Safety and Health - Germany - BetrSichV

No flammable liquids in accordance with BetrSichV

Water hazard class (WGK) obviously hazardous to water (WGK 2)

TRGS - 510 Storage Class Storage Class 3 : Flammable liquids

<u>Netherlands</u>

List of Carcinogenic, mutagenic and reproductive toxin substances in accordance with Inspectorate SZW (Netherlands)

Not Listed

Denmark

Registration number(s) (P-no.) No information available

Norway

Registration number(s) (PRN-no.) No information available

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture.

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 21/22



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H226 - Flammable liquid and vapour

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H400 - Very toxic to aquatic life

H412 - Harmful to aquatic life with long lasting effects

SVHC: Substances of Very High Concern for Authorisation:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT RE: Specific target organ toxicity - Repeated exposure

STOT SE: Specific target organ toxicity - Repeated exposure

EWC: European Waste Catalogue

LOW: List of Wastes (see http://ec.europa.eu/environment/waste/framework/list.htm)

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IATA: International Air Transport Association

ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air

IMDG: International Maritime Dangerous Goods

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

AGW Occupational exposure limit value BGW Biological limit value Ceiling Maximum limit value Sk* Skin designation

Date : 25-06-2024 VVFK(E) : 05/1516300

Rev : E Page : 22/22



Opgesteld door: NB	Bekrachtigd door: SL

Classification procedure		
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used	
Acute oral toxicity	Calculation method	
Acute dermal toxicity	Calculation method	
Acute inhalation toxicity - gas	Calculation method	
Acute inhalation toxicity - Vapour	Calculation method	
Acute inhalation toxicity - dust/mist	Calculation method	
Skin corrosion/irritation	Calculation method	
Serious eye damage/eye irritation	Calculation method	
Respiratory sensitisation	Calculation method	
Skin sensitisation	Calculation method	
mutagenicity	Calculation method	
Carcinogenicity	Calculation method	
Reproductive toxicity	Calculation method	
STOT - single exposure	Calculation method	
STOT - repeated exposure	Calculation method	
Acute aquatic toxicity	Calculation method	
Chronic aquatic toxicity	Calculation method	
Aspiration hazard	Calculation method	
Ozone	Calculation method	

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)

European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)

European Chemicals Agency (ECHA) (ECHA_API)

Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

NIOSH (National Institute for Occupational Safety and Health)

Organisation for Economic Co-operation and Development Environment, Health, and Safety Publications Organisation for Economic Co-operation and Development High Production Volume Chemicals Programme

Organisation for Economic Co-operation and Development Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Apr-2024

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Regulation (EC) No. 1272/2008 and Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.