Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 1/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Productname	Kelfort ® Primer WB
Article number	1516071-1516076
Producttype	Mixture
Regulation	(EC) No. 1907/2006 and (EC) No. 1272/2008

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use	Consumer use, Professional use, Industrial use
Uses advised against	None known.

1.3 Details of the supplier of the safety data sheet

Distributeur Ferney Group BV Postbus 24 1700 AA Heerhugowaard – The Netherlands T +31 (0)72-5765000 - F +31 (0)72-5765010 bedrijfsbureau@ferneygroup.nl - www.ferney.nl

1.4 Emergency telephone number

Noodtelefoon: +49(0)9366-907126 (ma-do 7.15-18.00 hour) or

: +31(0)88-7558000 (after worktime, exclusive use for doctors, pharmacists and government

institutions)

Country	Organisation/ Company	Address	Emergency number	Comments
The Netherlands	National Poisons Information Center	House post number B.00.118 PO Box 85500 3508 GA Utrecht	+31 88 755 80 00	For the sole purpose of informing healthcare professionals in the event of acute poisoning

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 2/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Warning! Hazardous respirable droplets may be formed when EUH211

sprayed. Do not breathe spray or mist.

Contains 1,2-benzisothiazol-3(2H)-one. May produce an EUH208

allergic reaction.

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Signal word (CLP) : Not applicable Hazard statements (CLP) : Not applicable.

Precautionary statements (CLP) : P102 - Keep out of reach of children.

P271 - Use only outdoors or in a well-ventilated area.

P280 - Wear protective gloves, protective clothing, eye protection.

P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

[Spray application; P261 - Avoid breathing spray.].

EUH-statements : EUH208 - Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

Child-resistant fastening : Not applicable Tactile warning : Not applicable

2.3. Other hazards

Other hazards which do not result in classification : None under normal conditions.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT and/or vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 3/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Talc substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ES, FI, FR, GB, GR, HR, HU, IE, IT, LT, LU, NL, PL, PT, RO, SE, SI, SK, IS, NO, MK, CH)	CAS-No.: 14807-96-6 EC-No.: 238-877-9	2,5 - 10	Not classified
Mica;Silicates (less than 1% crystalline silica): Mica (respirable dust);Glimmer;Mica # Mica;Mika (tinjac, liskum);Mika # Mica;云母粉尘 # Mica dust substance with national workplace exposure limit(s) (BE, CZ, ES, GB, IE, NL, PT, CH)	CAS-No.: 12001-26-2 EC-No.: 310-127-6 REACH-no: Exempt	2,5 – 10	Not classified
Calcium carbonate substance with national workplace exposure limit(s) (FR, HR, LV, PL, CH)	CAS-No.: 471-34-1 EC-No.: 207-439-9 REACH-no: 01-2119486795- 18	2,5 – 10	Not classified
Dipropylene glycol n-butylether substance with national workplace exposure limit(s) (CZ, DE, DK, ES, FI, FR, GB, IT, LT, NL, PL, SE, NO)	CAS-No.: 29911-28-2 EC-No.: 249-951-5 REACH-no: 01-2119451543- 42	1 – 2,5	Not classified
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540- 60	0,005 ≤ C < 0,036	Acute Tox. 4 (Oral), H302 (ATE=450 mg/kg bodyweight) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 (M=1)

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 4/19



Opgesteld door: NB	Bekrachtigd door: SL

Specific concentration limits:		
Name	Product identifier	Specific concentration limits (%)
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540- 60	(0,036 ≤ C < 100) Skin Sens. 1, H317

Comments

: This mixture contains ≥ 1% titanium dioxide (CAS 13463-67-7). The Annex VI classification of Titanium dioxide does not apply to this mixture according to its Note 10. There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Descrip	otion of first aid	measures

First-aid measures general

: In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and

seek medical advice.

First-aid measures after inhalation

 Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. Give nothing by mouth.

First-aid measures after skin contact

: Remove contaminated clothing. Wash skin thoroughly with soap and water or use

recognised skin cleanser. Do NOT use solvents or thinners.

First-aid measures after eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get

medical attention if irritation occurs.

First-aid measures after ingestion

: If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects

: No information is on file to date regarding acute and/or delayed post-exposure symptoms

and effects.

Symptoms/effects after inhalation

: Unwanted symptoms may include the following:

irritation of the respiratory tract

coughing

nausea or vomiting headache

drowsiness/fatigue dizziness/twistiness unconsciousness.

Symptoms/effects after skin contact

: Repeated exposure may cause skin dryness or cracking. Irritation. Redness.

Symptoms/effects after eye contact Symptoms/effects after ingestion

No specific data.No specific data.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically. Immediate specific treatment is necessary in case of poisoning.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 5/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical, CO2, alcohol-resistant foam or waterspray. dry sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Fire will produce dense black smoke. Exposure to decomposition products may cause a

health hazard. Appropriate breathing apparatus may be required.

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of

burns and injuries.

Hazardous decomposition products in case of fire : Carbon dioxide (CO2). Carbon monoxide. halogenated hydrocarbons. Metallic oxides.

5.3. Advice for firefighters

Precautionary measures fire : Cool closed containers exposed to fire with water.

Firefighting instructions : Local evacuation is necessary (for people in close proximity to the spillage area). Fight fire

from safe distance and protected location. Use water spray to cool exposed surfaces.

Protection during firefighting : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European

standard EN 469 will provide a basic level of protection for chemical incidents.

Other information : Dyke fire control water for later disposal and do not scatter the material. Prevent fire fighting

water from entering the environment.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 6/19



Opgesteld door: NB Bekrachtigd door: SL

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

: No smoking. Ventilate area. Do not breathe vapours.

6.1.2. For emergency responders

Emergency procedures

Protective equipment : Equip rescue crew with proper protection.

Emergency procedures : No smoking. Ventilate area. Do not breathe vapours.

6.2. Environmental precautions

Prevent soil and water pollution. Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Collect spillage.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak without risks if possible.

Methods for cleaning up

: Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

Other information

: Clean preferably with a detergent - avoid use of solvents.

6.4. Reference to other sections

See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 7/19



Opgesteld door: NB Bekrachtigd door: SL

Hygiene measures : Eating, drinking and smoking should be prohibited in areas where this material is handled,

stored and processed.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use appropriate container to avoid environmental contamination.

Storage conditions : Store in accordance with local regulations.

Storage temperature : 5 - 30 °C Store in a dry, well ventilated place away from sources of heat, ignition and direct

sunlight

Information on mixed storage : Store separately from oxidising agents and strongly alkaline and strongly acidic materials.

Storage area : Prevent unauthorised access.

Special rules on packaging : Containers which are opened must be carefully resealed and kept upright to prevent

leakage. Do not store in unlabelled containers.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Dipropylene glycol n-butylether (29911-28-2)		
United Kingdom - Occupational Exposure Limits		
WEL TWA (OEL TWA)	10 mg/m³ (Aerosols) Source: supplier	
Talc (14807-96-6)		
United Kingdom - Occupational Exposure Limits		
Local name	Talc	
WEL TWA (OEL TWA)	1 mg/m³ respirable dust	
WEL STEL (OEL STEL)	3 mg/m³	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	
Mica;Silicates (less than 1% crystalline silica): Mica (respirable dust);Glimmer;Mica # Mica;Mika (tinjac, liskum);Mika # Mica; 云母粉 尘 # Mica dust (12001-26-2)		
United Kingdom - Occupational Exposure Limits		
Local name	Mica	
WEL TWA (OEL TWA)	0,8 mg/m³ respirable 10 mg/m³ total inhalable	
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE	

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 8/19



Opgesteld door: NB Bekrachtigd door: SL

8.1.2. Recommended monitoring procedures

Monitoring methods

Monitoring methods

If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidancedocuments for methods for the determination of hazardous substances will also be required.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory protection must be worn.

8.2.2. Personal protection equipment

Personal protective equipment:

Gloves. Protective clothing. In case of splash hazard: safety glasses.

Personal protective equipment symbol(s):







8.2.2.1. Eye and face protection

Eye protection:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. Protective goggles (EN 166)

8.2.2.2. Skin protection

Skin and body protection:

Cotton or cotton/synthetic overalls or coveralls are normally suitable. Every part of the skin which had contact with the product should have been washed thoroughly. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 9/19



Opgesteld door: NB	Bekrachtigd door: SL

Hand protection:

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged contact, use rubber or neoprene gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, they should however not be applied once exposure has occurred.

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): polyethylene (PE), polyvinyl alcohol (PVA), Viton® (0.65mm) nitrile rubber (0.5mm)

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Other skin protection

Materials for protective clothing:

Appropriate footwear and any additional skin protection measures must be selected on the basis of the task being performed and the risks involved, and must be approved by an expert before using this product.

8.2.2.3. Respiratory protection

Respiratory protection:

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators. Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140).

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 10/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Colour : Various colours.
Odour : Characteristic.
Odour threshold : Not available

Melting point : 0 °C (Literature references)
Freezing point : 0 °C (Literature references)
Boiling point : 100 °C (Literature references)

Flammability : Not flammable in the presence of the following materials or conditions: open fire, sparks and

static discharge, heat and shock and mechanical impact.

Not highly flammable, but may catch fire if continuously exposed to flame or high

temperature.

Explosive properties : No dangerous reactions known.

Oxidising properties : No data available.

Lower explosion limit : Not available

Upper explosion limit : Not available

Flash point : Not applicable

Auto-ignition temperature : Not relevant/applicable due to nature of the product.

Decomposition temperature : When exposed to heat, may decompose liberating hazardous gases

pH : 8 – 9 (ISO 19396-1:2017)

Viscosity, kinematic : 1278 mm²/s (Calculated value)

Viscosity, dynamic : 95 – 100 KU (Krebs Stormer) @20°C

Solubility : Miscible with water.

Partition coefficient n-octanol/water (Log Kow) : Not applicable

Partition coefficient n-octanol/water (Log Pow) : Not applicable

Vapour pressure : Not relevant/applicable due to nature of the product.

Vapour pressure at 50°C : Not available

Density : ≈ 1,33 g/cm³ Calculated value (ISO 2811-1:2016)

Relative density : Calculated value (ISO 2811-1:2016)

Relative vapour density at 20°C : 1 (Literature references)

Particle characteristics : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : Not available

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 11/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under recommended handling and storage conditions (see section 7).

10.3. Possibility of hazardous reactions

Keep away from oxidising agents and strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

10.4. Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

10.5. Incompatible materials

See Heading 7.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Combustion generates: Toxic gases. Carbon oxides (CO, CO2). fume.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified Acute toxicity (inhalation) : Not classified

Dipropylene glycol n-butylether (29911-28-2)	
LD50 oral	4000 mg/kg bodyweight
LD50 dermal	> 2000 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	> 2040 mg/l
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	490 mg/kg (OECD 401 method)
LD50 oral	1020 mg/kg bodyweight

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 12/19



Opgesteld door: NB	Bekrachtigd door: SL

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l
Calcium carbonate (471-34-1)	
LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 420 (Acute Oral Toxicity - Fixed Dose Method), Guideline: EU Method B.1 bis (Acute Oral Toxicity - Fixed Dose Procedure)
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal))
LC50 Inhalation - Rat	> 3 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Guideline: EU Method B.2 (Acute Toxicity (Inhalation)), Guideline: EPA OPPTS 870.1300 (Acute inhalation toxicity)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	pH: 8 – 9 (ISO 19396-1:2017) : Not classified pH: 8 – 9 (ISO 19396-1:2017)
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
NOAEL (animal/male, F0/P)	112 mg/kg
NOAEL (animal/female, F0/P)	112 mg/kg
NOAEL (animal/female, F1)	56,6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.380 (Reproduction and Fertility Effects)
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

1,2-benzisothiazol-3(2H)-one (2634-33-5)

Rev : C Page : 13/19



Opgesteld door: NB	Bekrachtigd door: SL

NOAEL (subacute, oral, animal/female, 28 days)	150 mg/kg bodyweight (OECD 407 Method)
Calcium carbonate (471-34-1)	
NOAEL (oral, rat, 90 days)	1000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	≥ 0,212 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Aspiration hazard :	Not classified
Kelfort Primer WB	
Viscosity, kinematic	1278 mm²/s (Calculated value)
Dipropylene glycol n-butylether (29911-28-2)	
Viscosity, kinematic	4,9 mm²/s

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

No additional information available

11.2.2. Other information

Potential adverse human health effects and symptoms : This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 14/19



Opgesteld door: NB Bekrachtigd door: SL

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The mixture has been assessed following the conventional method of the Regulation (EC)

No. 1272/2008 [CLP] and is not classified as dangerous for the environment. See Sections

2 and 3 for details.

Hazardous to the aquatic environment, short-term

acute)

: Not classified

Hazardous to the aquatic environment, long-term

(chronic)

: Not classified

Dipropylene glycol n-butylether (29911-28-2)		
LC50 - Fish [1]	841 mg/l	
EC50 - Crustacea [1]	> 100 mg/l Test organisms (species): Daphnia magna	
EC50 - Other aquatic organisms [1]	> 1000 mg/l waterflea	
EC50 96h - Algae [1]	519 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)	
1,2-benzisothiazol-3(2H)-one (2634-33-5)		
LC50 - Fish [1]	2,18 mg/l	
LC50 - Fish [2]	2,18 mg/l Test organisms (species): Oncorhynchus mykiss (previous name: Salmo gairdneri)	
EC50 - Crustacea [1]	2,94 mg/l Test organisms (species): Daphnia magna	
EC50 - Crustacea [2]	2,9 mg/l Test organisms (species): Daphnia magna	
EC50 - Other aquatic organisms [1]	2,94 mg/l waterflea	
EC50 - Other aquatic organisms [2]	0,11 mg/l	
EC50 72h - Algae [1]	0,11 mg/l pseudokirchneriella subcapitata	
Calcium carbonate (471-34-1)		
EC50 72h - Algae [1]	> 14 mg/l Test organisms (species): Desmodesmus subspicatus (previous name: Scenedesmus subspicatus)	

12.2. Persistence and degradability

Kelfort Primer WB		
Persistence and degradability	There are no data available on the preparation itself. This product has not been tested for biodegradation.	
Dipropylene glycol n-butylether (29911-28-2)		
Persistence and degradability	Rapidly degradable	
1,2-benzisothiazol-3(2H)-one (2634-33-5)		
Persistence and degradability	Not rapidly degradable	
Biodegradation	85 % (OECD 301C method)	
Calcium carbonate (471-34-1)		
Persistence and degradability	Rapidly degradable	

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 15/19



Opgesteld door: NB Bekrachtigd door: SL

Talc (14807-96-6)	
Persistence and degradability Rapidly degradable	
Mica;Silicates (less than 1% crystalline silica): Mica (respirable dust);Glimmer;Mica # Mica;Mika (tinjac, liskum);Mika # Mica;云母粉尘 # Mica dust (12001-26-2)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

Kelfort Primer WB		
Partition coefficient n-octanol/water (Log Pow)	Not applicable	
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
Bioaccumulative potential	There are no data available on the preparation itself.	
Dipropylene glycol n-butylether (29911-28-2)		
Partition coefficient n-octanol/water (Log Pow)	1523	
1,2-benzisothiazol-3(2H)-one (2634-33-5)		
Partition coefficient n-octanol/water (Log Pow)	0,7	

12.4. Mobility in soil

Kelfort Primer WB	
Ecology - soil	There are no data available on the preparation itself.

12.5. Results of PBT and vPvB assessment

Kelfort Primer WB

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

Additional information

: Do not allow to enter drains or water courses. May pollute drinking water.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 16/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation Waste treatment methods

- : Do not allow to enter drains or water courses.
- : The generation of waste should always be avoided or kept to a minimum wherever possible. Disposal of this product, solutions and any by-products should always be in accordance with the applicable environmental protection and waste disposal legislation and any other regional or local regulations. Have surplus and non-recyclable products disposed of by a licensed disposal company. Do not dispose of untreated waste through the sewer unless in full compliance with the requirements of the competent authorities.

Product/Packaging disposal recommendations

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

European List of Waste (LoW, EC 2000/532)

: 08 01 11* - waste paint and varnish containing organic solvents or other dangerous

substances

08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

08 01 15* - aqueous sludges containing paint or varnish containing organic solvents or other

dangerous substances 15 01 02 - plastic packaging 15 01 06 - mixed packaging

HP Code

: HP7 - "Carcinogenic:" waste which induces cancer or increases its incidence

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 17/19



Opgesteld door: NB Bekrachtigd door: SL

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information	n available			

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 18/19



Opgesteld door: NB	Bekrachtigd door: SL

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Dual-Use Regulation (428/2009)

Contains no substance subject to the COUNCIL REGULATION (EC) No 428/2009 of 5 May 2009 setting up a Community regime for the control of exports, transfer, brokering and transit of dual-use items.

VOC Directive (2004/42)

Decopaint Directive (2004/42/EC) - Annex II : A/d (Paints and Varnishes - Interior/exterior trim and cladding paints for wood and metal)

Maximum Allowable Concentration : 130 g/l VOC Maximum content of VOC : 20,00 g/l VOC

Seveso Directive (Disaster Risk Reduction)

Seveso Additional information : This product is not covered by the Seveso Directive.

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

Date : 16-07-2024

VVFK(E): 11/1516071-1516076

Rev : C Page : 19/19



Opgesteld door: NB	Bekrachtigd door: SL

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
2	Hazards identification	Modified	
3.2	Composition/information on ingredients	Modified	
11	Toxicological information		
12.	2. Ecological information		

Full text of H- and EUH-statements:		
Acute Tox. 4 (Oral)	. 4 (Oral) Acute toxicity (oral), Category 4	
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1	
EUH208	Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.	
EUH210	Safety data sheet available on request.	
EUH211	EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.	

Full text of H- and EUH-statements:		
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
H302	Harmful if swallowed.	
H315	Causes skin irritation.	
H317	May cause an allergic skin reaction.	
H318	Causes serious eye damage.	
H400	Very toxic to aquatic life.	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
Skin Sens. 1	Skin sensitisation, Category 1	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
EUH211	EUH211	On basis of test data
EUH208	EUH208	Calculation method

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.